

Product data sheet

OUTDOOR LIGHTING
V1-S1-90442-40U30-6621050 TORNADO URBAN 210W 5000K NEMA
VARTON




IP
66

IK
09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: roads and streets. Installation: pole and side-entry mounted (Ø48mm-60mm). Ingress protection (IP): IP66 Impact resistance: IK09 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: YXJ11 Mounting method: Side-entry Suitable for top end size, mm: 48...60 Power factor: 0,97 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-urban-dlya-goroda/svetodiodnyy-svetilnik-var-ton-ulichnyy-tornado-kreplenie-na-konsol-210-vt-5000-k-1-10v-nema-ral9005-/>

Light output 1



1 x LED			
Nominal lamp power	210 W	LOR	100%
Lamp flux	28350 lm	Total flux	28350 lm
Luminous efficacy	135 lm/W	Total power	210 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 34.29 in
Width: 13.78 in
Height: 5.00 in

Adjustability

Fixed

Electric

System power: 210 W

Protection

IP: 66
IK: 09