Product data sheet


ROTAO60 227-561K-10GEE/830, W
227-561K-10GEE/830
HALLA



IP 20


227-561K-10GEE/830, W Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 603 x 603 x 65 mm Type of installation: Suspended Distribution: Direct-indirect Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.9 W	CRI	80
Total flux	318 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	2.9 W

Mounting mode

Pendant

Shape and measurements

Height: 2.56 in

Diameter: 23.74 in

Adjustability

Fixed

Electric

System power: 29 W

Appliance Class: I

Protection

IP: 20