



Product data sheet

X-LINE SLIGHT SURFACE LED 2200 PLX EDD 24 840 LINE-1BM / L-570MM
19.4424.D223.24
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is aluminum. Colour - anodised aluminum. Dimensions: 570 x 34 x 68 mm. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,50%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 1796,3 lm. Power of luminaire: 13,4 W. Luminaire's light efficiency: 134,1 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 14 (B10), 24 (B16), 22 (C10), 36 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	13.4 W	LOR	52%
Lamp flux	2395 lm	Total flux	1256 lm
Luminous efficacy	179 lm/W	Total power	13.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.44 in

Width: 1.34 in

Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 13.4 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F