
Product data sheet


L101_2M_LED_36W_NEUTRAL_L1194MM
372613
PETRIDIS



IP 20 IK 02

Technical Features - Steel body with flat form, electrostatically painted in white colour. - UGR ≤ 19 for 2M Louvre versions. - High efficient opal PMMA for plexi version and aluminium louvre with high efficient satin PMMA cover for louvre version. - Last generation high efficient LED CHIP. - Pure light without IR/UV radiation. - Connection for operation on 230V-50/60Hz. High Efficiency - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). High Output - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B50). Upon request: - Body and accessories in various colours (RAL) - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	36 W	LOR	63%
Lamp flux	5860 lm	Total flux	3670 lm
Luminous efficacy	163 lm/W	Total power	36 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.01 in
Width: 4.41 in
Height: 3.15 in

Adjustability

Fixed

Design

Material impression: Chrome, Gloss

Electric

System power: 36 W
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 20
IK: 02
Designation labels: CE