


Product data sheet

GOLAS MIDI
911401.004
RZB



Series: Golas Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Passive cooling. Rotates 356° horizontally and swivels 65° vertically. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools. LED included. Connected converter included in separate gearbox. Available Colours: silver Type of Installation: Recessed ceiling mounting Dimensions: D 155, H 4, HE 130 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 2700K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 3250lm System power: 36W Beam Angle: 38° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 18,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	36 W	CRI	80
Total flux	3250 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	36 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.04 in
Diameter: 6.10 in

Adjustability

Rotatable, Tilttable

Electric

System power: 36 W

Protection

IP: 20