


Product data sheet

EMERGENCY EMERGENCY LUMINAIRE, OPAL COVER
EM1402302-50-40
SCHMITZ | WILA



Emergency LED 4000 K Emergency Luminaire, Light distribution direct Opal Cover Spherical design Luminaire housing Aluminium-Finish
Product: EM1402302-50-40 Light Technique Colour rendering Index CRI > 75 Colour temperature 4000K Lifetime 50.000 h (L70)) Luminaire
luminous flux in case of emergency: 200 Llm Luminaire housing Housing made of aluminium Finished Aluminium Opal cover (PMMA),
spherical design Operating and assembly technology LED control gear, standard Self-contained systems with integrated battery, type: 6.0V
4.0Ah NiMH Plug-in terminals for through wiring up to 4 x 2.5 mm² Maintained operation (mains + 3hr emergency) Suitable for ceiling and wall
installation Twist on front Lamp Wattage: 21 W Colour Rendering Index: 75 Colour Temperature: 4000 K Luminaire Luminous Flux: 1360 Llm
System Efficiency: 50 Llm/W Luminance $\gamma \geq 65^\circ$: <3000 cd/m² UGR: 21 Number Luminaires LZ: 0.12 Connector: plug-in terminal, 4 x 2.5 mm²
Diameter D: 395 mm Height: 113 mm Total Weight: 2.6 kg Degree of Protection IP20 CE-Sign Total system: Protection class 1 Data record
EM1402302-50-40

Light output 1



1 x General service incandescent lamp			
Nominal lamp power	27 W	LOR	100%
Lamp flux	1360 lm	Total flux	1360 lm
Luminous efficacy	50 lm/W	Total power	27 W
CCT	4000 K		
CRI	75		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.45 in
Diameter: 15.55 in

Adjustability

Fixed

Electric

System power: 27 W
Appliance Class: I

Protection

IP: 20