


Product data sheet

AJ 50 WALL LED 3000K 7.6W
91338-1002
LOUIS POULSEN



AJ 50 Wall Design: Arne Jacobsen Concept: The fixture emits downward directed light. The shade is painted white on the inside to ensure a soft comfortable light distribution. Finish: White, black or aluminium coloured with textured surface, powder coated. Materials: Shade: Die cast aluminium. Wall box: Die cast aluminium. Arm: Die cast aluminium. Mounting: Terminal block: 1x3x2.5mm². Cable entries: 2x bottom + 3x rear entries for Ø 10-14.5mm cable. Looping: Approved, max. 3x1,5mm². Class: Ingress protection IP65. Electric shock protection I w. ground. IK06. Sizes and weights: Width x Height x Length (mm) 349 x 248 x 160 Max 2.0 kg Information: Compatible with leading edge mains dimmers. Please note that low power consumption on some products can affect dimming properties. This product is fitted with an integrated energy-saving LED light source. Should you wish to replace it, please contact Louis Poulsen so we can help you purchase the correct LED Replacement Kit. Please note that LED-replacement should always be carried out by an authorised electrician.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.6 W	CRI	90
Total flux	428 lm	LOR	69%
Luminous efficacy	56 lm/W	Total power	7.6 W

Mounting mode

Wall mounted

Shape and measurements

Length: 13.74 in
Width: 6.30 in
Height: 9.84 in

Adjustability

Fixed

Electric

System power: 7.6 W
Appliance Class: I

Protection

IP: 65
IK: 06