Product data sheet


DEECOS S MINI TRACK-IN
742265.004
RZB



IP 20 IK 06


Series: DEECOS S mini track-in LED surface-mounted projector in modern design with no visible cooling ribs. Housing made of die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. With multi adapter for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. MultiLumen: Luminous flux adjustable in 4 steps. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: silver Diameter: 87 mm Height: 130 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 12 W Rated luminous flux: 1200 lm Beam angle Down: 40° / 28° Luminous efficiency: 100 lm/W System power 2: 18 W Rated luminous flux 2: 1800 lm Luminous efficiency 2: 100 lm/W System power 3: 28 W Rated luminous flux 3: 2700 lm Luminous efficiency 3: 96 lm/W System power 4: 30 W Rated luminous flux 4: 2850 lm Luminous efficiency 4: 95 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2700 lm	ULOR	13%
Luminous efficacy	96 lm/W	Total flux	2700 lm
CCT	3000 K	Total power	28 W
CRI	90		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1800 lm	ULOR	13%
Luminous efficacy	100 lm/W	Total flux	1800 lm
CCT	3000 K	Total power	18 W
CRI	90		



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1200 lm	ULOR	13%
Luminous efficacy	100 lm/W	Total flux	1200 lm
CCT	3000 K	Total power	12 W
CRI	90		



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2850 lm	ULOR	13%
Luminous efficacy	95 lm/W	Total flux	2850 lm
CCT	3000 K	Total power	30 W
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.31 in

Diameter: 3.43 in

Adjustability

Rotatable, Tiltable

Electric

System power: 12-30 W

Protection

IP: 20

IK: 06