


Product data sheet

LD48 2.3W 700MA MB
LD48-C1-700-MB
LIGHTGRAPHIX



LD48 Ø63mm Recessed Wall Light. Constant Current. 2.3W 700mA 31° Medium beam. The LD48 has been updated with the latest LED technology and fitted with our new optics. The lens assembly is recessed and inclined by 20° for a floor wash illumination with minimal glare. This is a high-quality fitting with a machined 316 stainless steel bezel and black anodized body, for interior and exterior use. It has no visible fixings and the glass is fixed with a hidden gasket, so no unsightly glue line is visible. A choice of beam angles and colour temperatures are available.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.34 W	CRI	93
Total flux	177 lm	LOR	100%
Luminous efficacy	76 lm/W	Total power	2.34 W

Mounting mode

Wall recessed

Shape and measurements

Height: 1.50 in
Diameter: 2.48 in

Adjustability

Fixed

Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 2.34 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F