

Product data sheet


LEDDOWNLIGHTRC-HM R82-5W-5700-WH-GP
140048186
OPPLE



IP
20

Housing:corrosionresistant cast aluminium; Reflector: High reflective material; Mounting ring: plastic, white; Installation: recessed; Dimensions:Φ90×47mm; Ceiling cutouts:Φ80mm; Power:5W; Lamp(s):LED 830; Colour temperature:5700K; Colour rendering:RA80; Total luminous flux of luminaire:400lm; Beam angle:75°; Light distribution:Lambert; Service life:30,000h at 70% luminous flux; Degree of protection:IP20(IP44 for exposed parts); Class of protection II; Mains voltage:220-240V/50-60Hz; Two fixing clips provided for tool-free installation in ceilings of thickness 5-25 mm

Light output 1



1 x LED			
Nominal lamp power	4.9 W	LOR	100%
Lamp flux	367 lm	Total flux	367 lm
Luminous efficacy	75 lm/W	Total power	4.9 W
CCT	5700 K		
CRI	80		

Mounting mode

Ceiling recessed

Electric

System power: 4.9 W

Shape and measurements

Length: 3.54 in
Width: 3.54 in
Height: 1.85 in

Protection

IP: 20

Adjustability

Fixed