



# Product data sheet

PLANOX  
672205.009  
RZB



Item Number: 672205.009 Series: Planox Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic polycarbonate, prepared for two suspension chains or cables (suspension provided on site), interior fastening element made of sheet steel, painted white, converter integrated, refractor plastic (PMMA), opal, prismatic inside, refractor attached using retaining clips made of stainless steel. Single battery system with integrated self-test as standard, lamp (LED) included. Available Colours: light grey (RAL 7035) Type of Installation: Ceiling mounting, Suspension cable/chain, Wall (surface) Dimensions: L 1573, B 96, H 100mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: automatic self-test Safety Marks: D-mark, F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4100lm System power: 37W Beam Angle: 127°/98° Number of fittings B10A: 21 Number of fittings B16A: 34 Inrush current: 16A Unified Glare Ratio: 23,3 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	4100 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	7%
		Total power	38 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 3.78 in  
Width: 61.93 in  
Height: 3.94 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 38 W

## Protection

IP: 66  
IK: 03