Product data sheet


METEOR V2 LED COMPACT 3000 MICRO-PRM EDD 04 840 L-620MM
19.4367.2523.04
LUXIONA



IP 20 IK 04

Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9005 (black). Dimensions: 620 x 209 x 64 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 85,00%. Beam angle: (C0-C180) / (C90-C270) - 84,2° / 91,4°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 2595 lm. Power of luminaire: 19 W. Luminaire's light efficiency: 136,6 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 20 (B10), 31 (B16), 33 (C10), 53 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	19.3 W	LOR	52%
Lamp flux	3057 lm	Total flux	1603 lm
Luminous efficacy	158 lm/W	Total power	19.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in
Width: 8.23 in
Height: 2.52 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 19.3 W
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F