


Product data sheet

LTUB60 SUT 840 2200 9WW TECH BK
L61ST084M0TE930NB
LAMP




IP
20

IK
07

"Luminaire to be installed on a suspended rail, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 840 mm,with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare level, less than UGR16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette. Compatible with Lamp Nomadic system. "

Light output 1



1 x LED			
Nominal lamp power	13.7 W	LOR	100%
Lamp flux	1260 lm	Total flux	1259 lm
Luminous efficacy	92 lm/W	Total power	13.7 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 34.02 in

Width: 2.76 in

Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 13.7 W

Appliance Class: 0

Protection

IP: 20

IK: 07