



Product data sheet

SYSTEM BATTEN LUMINAIRE CHANNEL S MASTER XHE (EXTREME HIGH EFFICIENCY) 12.8W CRI > 80 3000K MASTER EN 2004.9784 - CHAN-S INS1500 XHE LED-830 DIR DALI MASE
REGENT




System batten luminaire Channel S Master xHE (extreme High Efficiency), with LED, system power: 12.8 W, standby power 0.5 W, luminous flux of luminaire with optics RUN opal 1280 lm, with optics RUN+ 1040 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, Photobiological safety: Safe., 230 V, nominal current: 0.06 A, direct light emission, quick connect system, pre-wired, Master END, 1 integral control gear, DALI, support profile, optics and system components to be ordered separately xHE: Non-extendable, with through-wiring protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08 for ambient temperatures -5 to +30 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1028206 L = 1500 mm, B = 65 mm, H = 60 mm


Light output 1



1 x LED			
Nominal lamp power	27.4 W	LOR	100%
Lamp flux	1120 lm	ULOR	10%
Luminous efficacy	41 lm/W	Total flux	1120 lm
CCT	3000 K	Total power	13 W
CRI	80		



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	1040 lm	ULOR	10%
Luminous efficacy	22 lm/W	Total flux	1040 lm
CCT	3000 K	Total power	13 W
CRI	80		



1 x LED			
Nominal lamp power	27.4 W	LOR	100%
Lamp flux	1280 lm	ULOR	10%
Luminous efficacy	47 lm/W	Total flux	1280 lm
CCT	3000 K	Total power	12.8 W
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 59.06 in

Width: 2.56 in

Height: 2.40 in

Weight: 1.13 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 12.8-13 W

Appliance Class: I

Protection

IP: 20

IK: 08