


Product data sheet

CIRCULUS BLACK 1420LM 2700K RA>80 TRAILING EDGE DIMMING
7021982140006
SG ARMATUREN



Round surface-mounted luminaire, wholly uniform light with attractive design, made of powder-coated aluminium, simple to mount by removing the back plate, which can be screwed on to all known ceiling outlets/electrical boxes, clips with option of additional looping, connectors between lamp and mounting plate, dimmable driver phase-dimming/DALI and sensor options. Both visible and hidden cabling possible. Light distribution Direct Light technic LED 15W 2700K Ra>80 SDCM 3 L80/B10 >50,000 hrs L70/B50 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP21 Materials and finish Housing: Steel Colour: Black (RAL 9004) Optics: Acrylic (PMMA) Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light output 1



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	1420 lm	ULOR	21%
Luminous efficacy	95 lm/W	Total flux	1420 lm
CCT	2700 K	Total power	15 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.17 in
Width: 14.17 in
Height: 1.77 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 15 W
Appliance Class: I

Protection

IP: 21