


# Product data sheet

MINITONDO 800 1 X 11.9W 360° 4000 K  
GH1417.BRXT400EN  
GHIDINI



Series of bollards with minimal design available in various sizes and heights. Designed to illuminate avenues, walkways, pathways, gardens and parks without glaring, it is available with two types of emission: 360 ° or 180 °. The construction of high oxidation resistant aluminum alloy which is subjected to nano-bonderite treatment and finished with texturized polyester powder paint, making the product resistant to atomospheric agents and UV rays, guaranteeing maximum protection over the years. Silicone gaskets ensure maximum sealing in all operating and temperature conditions. The diffuser in polycarbonate makes the product vandal resistant. The product is installed with stainless steel screws on an anchor plate previously anchored to the ground. The product is equipped with the Ghidini water-lock system that prevents the rising of humidity from the power cable due to the alternating on and off cycles.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	90
Total flux	154 lm	LOR	100%
Luminous efficacy	13 lm/W	ULOR	16%
		Total power	12 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 2.36 in

Width: 2.36 in

Height: 28.98 in

## Adjustability

Fixed

## Electric

System power: 12 W

Appliance Class: II

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 65