
Product data sheet

CITYSOUL GEN2 LED MINI BGP530 T25 1 XLED19-4S/727 DM50
BGP530
PHILIPS



CitySoul LED gen2 - a versatile identity CitySoul gen2 LED is one of the most versatile and inspirational urban street lighting families designed by Philips to date. This highly efficient range delivers excellent lighting levels whilst also providing the right ambiance for all urban application areas, from the outskirts of the city right through to the city center. By evolving the modularity of the CitySoul family and adding new innovations like the Lyre and the Accent bracket, Philips has made this range the ideal toolbox for every urban context. The design is flatter, completely round, and the transitions with the spigot and bracket entirely flush, thereby giving your cityscape a coherent, elegant and discreet identity. Designed around its LED engine, CitySoul gen2 LED is highly efficient and easy to maintain. It comes in two sizes and is suitable for side-entry, post-top, catenary and suspended mounting. Thanks to the built in Philips Ledgine optimized LED platform, and the wide range of available application-tailored optics, CitySoul LED gen2 delivers the right amount light and in the right direction on your street, enabling further energy savings. The luminaire comes with one or two Philips SR (System Ready) sockets, which makes the luminaire future ready. What this means is that CitySoul LED gen2 is ready to be paired with both standalone and advanced control and lighting software applications such as Interact City from Signify. Next to this, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door or directly on the luminaire, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, and enabling you to create your digital library of lighting assets and spare parts. CitySoul LED gen2 can also be equipped with our dedicated light recipe that preserves a dark night sky.

Light output 1



1 x LED

Nominal lamp power	14.4 W	LOR	86%
Lamp flux	1900 lm	Total flux	1638 lm
Luminous efficacy	114 lm/W	Total power	14.4 W
CCT	2700 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in
Diameter: 21.26 in

Electric

System power: 14.4 W