

Product data sheet

OFFICE LUMINAIRES FOR SPECIAL CEILINGS
V1-A1-00363-10000-2003640 AL220 IP20 (1170*100MM) 35W 4000K
VARTON




IP
20

IK
02

Luminaire for rack ceiling system. Stainless steel housing with white powder coating. Application: administrative facilities, lobbies. Recessed mounted compatible with rack ceiling with rails of Italian and German design. Length, mm: 1 170 Width, mm: 100 Height/depth, mm: 50 Power factor: 0,95 Input voltage (AC, 50Hz), V: 176...264 Ingress protection (IP): IP20 Impact resistance: IK02 Protection class: I AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YX/J4 <https://www.varton.ru/products/ofisnye-svetilniki-dlya-nestandardnykh-potolkov/al-svetilniki-dlya-reechnykh-potolkov/al220-ip20-reechnyy-p-k-1170-100mm-analog-1-36/svetodiodnyy-svetilnik-var-ton-dlya-reechnogo-potolka-1170kh100-35-vt-4000-k-ip20/>

Light output 1



1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	2793 lm	Total flux	2793 lm
Luminous efficacy	80 lm/W	Total power	35 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.06 in
Width: 3.94 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 20
IK: 02