Product data sheet

ALU-QUADRAT 251046.003.1

RZB








Series: Alu-Quadrat Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 280, B 280, H 120 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1250Im System power: 27W Beam Angle: 133°/133° Unified Glare Ratio: 19,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	80
Total flux	1250 lm	LOR	100%
Luminous efficacy	46 lm/W	ULOR	21%
		Total power	27 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.02 in Width: 11.02 in Height: 4.72 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 27 W

Protection

IP: 43 IK: 02