


Product data sheet

BEAMLITE II 2X200LM 3H AT (DATA FOR ONE LAMP HEAD ONLY)
BL2MD-C3-AT
EATON EMERGENCY LIGHTING




• High flux luminaire with configuration of two directional LED lamp heads • Variants of 200lm, 400lm and 800lm, each light head can reach up to 400 lumens maximum • Installation up to 25m (30m) with optimum spacing of 34.6m (40.28m) for 1lux (0.5lux) illumination • E-focus programming. Narrow and Wide light distribution, programmed by the user • One product applicable for Escape Route or Open area illumination • User / installer to define light distribution to fit the application • Suitable for use in large open areas (supermarkets, warehouses, cinemas, theatres, factories, shopping malls, industrial units and stadiums etc.) • New modern and flexible / modular design, wall mounted or recessed (via accessory) • Mains & communication cabling option from all housing sides (back & side entry) • Locking mechanism of light head preventing accidental change of light heads configuration

Light output 1 (emergency)



1 x LED			
Nominal lamp power	1.6 W	LOR	100%
Lamp flux	200 lm	Total flux	200 lm
Luminous efficacy	125 lm/W	Total power	1.6 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	1.6 W	LOR	100%
Lamp flux	200 lm	Total flux	200 lm
Luminous efficacy	125 lm/W	Total power	1.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 0.39 in
Diameter: 4.69 in

Adjustability

Fixed

Electric

System power: 1.6 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Single battery 3 h
Emergency sign: N/A

Protection

IP: 65

IK: 07