# Product data sheet


BALDER INF W90 L1200 840
7023108
EXAKTOR



IP 21

Balder INF är en interiörbelysning främst avsedd för infällning i undertak men kan även monteras dikt tak med tillbehör. Armaturen är lämplig som belysning på arbetsplatsen, i butik, skola, korridor, med mera. Balder INF har en unik optik med en reflektor för varje ljuskälla, vilket ger en mycket effektiv avbländningsvinkel. Monteringen är enkel, Balder INF vilar på ramverket i undertaket vilket möjliggör att armaturen enkelt kan placeras på valfri plats. Balder INF finns med färgtemperatur 3000K eller 4000K och som alternativ med en eller två belysningsenheter (1R/2R). Armaturen finns i olika storlekar, 600, 1200, 600x600, 600x300, 1200x300 samt 1200x600mm. På förfrågan kan armaturen fås med extra högt ljusflöde, HO. Armaturen finns som on/off, DALI eller med Active Ahead, samt med symmetrisk eller asymmetrisk ljusbild. Armaturen tillverkas i Värnamo.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 30 W | CRI | 80 |
| Total flux | 4892 lm | LOR | 100% |
| Luminous efficacy | 163 lm/W | Total power | 30 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 47.05 in
Width: 3.94 in
Height: 0.47 in

### Adjustability

Fixed

### Electric

System power: 30 W
Ballast: ECG

### Protection

IP: 21
Designation labels: CE