


Product data sheet

VIGILANT LED HIGH EFFICIENTCY HIGH BAY 39500 LUMENS, OVAL DISTRIBUTION, CLEAR POLYCARBONATE LENS
 VEU4EN2JXXXXXXN
 DIALIGHT



Vigilant LED High Efficiency High Bay 39,500 Lumens 228 Watts 100-277V AC, 120-250V DC Neutral White, 80CRI Clear Polycarbonate Lens
 UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK06 Oval
 Distribution IP66/67 LM-79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	229.9 W	CRI	84
Total flux	35884 lm	LOR	100%
Luminous efficacy	156 lm/W	Total power	229.9 W

Mounting mode

Pendant

Shape and measurements

Height: 3.00 in

Diameter: 15.96 in

Adjustability

Rotatable, Tilttable

Electric

System power: 229.9 W

Appliance Class: I

Protection

IP: 66

IK: 06