


# Product data sheet

PURE 1 SPOT PRO CEILING  
09.1172/Hi PAR 51/35W/10°/25°/40°  
FLOS




Spotlight to be installed on ceiling for discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation. Electronic control gear 220/240V, 50/60Hz integrated.


## Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2194 lm	LOR	49%
Luminous efficacy	63 lm/W	Total flux	1072 lm
CCT	3000 K	Total power	35 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2297 lm	LOR	50%
Luminous efficacy	66 lm/W	Total flux	1144 lm
CCT	3000 K	Total power	35 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2441 lm	LOR	54%
Luminous efficacy	70 lm/W	Total flux	1315 lm
CCT	3000 K	Total power	35 W
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 35 W  
Appliance Class: I

#### Shape and measurements

Length: 1.69 in

Width: 4.34 in

Height: 5.31 in

#### Adjustability

Free

#### Protection

IP: 20