

# Product data sheet

LUCAS IV (WALL FITTING BEADED)  
9.834.3142.16  
LEIPZIGER LEUCHTEN



IP  
55

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	83%
Lamp flux	2000 lm	ULOR	2%
Luminous efficacy	28 lm/W	Total flux	1658 lm
CCT	3400 K	Total power	59 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	83%
Lamp flux	4000 lm	ULOR	2%
Luminous efficacy	37 lm/W	Total flux	3316 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 22.44 in  
Diameter: 22.44 in

## Electric

System power: 59-89 W

## Protection

IP: 55