Product data sheet

VIVO M LED4100-840 TEC-GP WFL-S WHM
60714277
ZUMTOBEL



LED spotlight with stabilised colour temperature "Essential stableWhite"; optimised for efficient and high-output accent lighting for shops and showrooms; compact, timeless spotlight design; innovative thermal design achieves passive cooling; Luminaire with TECTON GP (grand profile) adapter for simple, rapid mounting of luminaire to TECTON continuous-row systems, ; lamp(s): 1/36W LED4100-840; Colour rendering Ra > 80, colour temperature 4000 K (neutral white); Luminaire or spotlight with WIDE FLOOD light distribution, with rotationally symmetrical reflector in silver colour; Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 4100 lm, Luminaire efficacy: 114 lm/W; service life: 50000 h for luminous flux at 80% of initial value; UVA-free and IR-free light; total power: 36 W; with converter, mains voltage: 220-240V/ 50/60Hz; spotlight can rotate through 360° and tilt through 90°; spotlight housing made of die-cast aluminium, surface finish: microtextured paint in white; excellent glare reduction via front ring of polycarbonate, black; front ring used for attaching accessories; specular reflector made of polycarbonate aluminium-sputtered, mirrorbrite, iridescent-free; specular reflector designed to be interchangeable and retrofitted; track unit: 498 mm long; spotlight fastened using CLIX technology; dimensions: 100x498x205 mm; weight: 1.8 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	4100 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	36 W

Mounting mode

Pendant

Shape and measurements

Length: 3.94 in
Width: 19.61 in
Height: 8.07 in
Weight: 1.8 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 36 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE