Product data sheet


RICHARD II (WALL FITTING) 9.844.2152.00

LEIPZIGER LEUCHTEN



Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1	x High	pressure	sodium	vapour	lamp
---	--------	----------	--------	--------	------

IP 55

Nominal lamp power	50 W	LOR	43%
Lamp flux	3500 lm	ULOR	8%
Luminous efficacy	24 lm/W	Total flux	1504 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High	pressure	sodium	vapour	lamp

Nominal lamp power	70 W	LOR	43%
Lamp flux	5600 lm	ULOR	8%
Luminous efficacy	29 lm/W	Total flux	2407 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode	Electric
Wall mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 9.84 in	IP: 55
Diameter: 9.84 in	