Product data sheet


PURA SPOT S MAXI
741822.002.1.76
RZB



IP 20 IK 03

Series: Pura Spot S Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 180° vertically, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling, with DALI adapter for RZB 230V 3 circuit DALI tracks. LED included. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Track on ceiling Dimensions: L 227, B 146, H 145 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2850lm System power: 27W Beam Angle: 15° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 18,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	80
Total flux	2850 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	27 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.75 in
Width: 8.94 in
Height: 6.06 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 27 W

Protection

IP: 20
IK: 03