Product data sheet

LUCAS III (WALL FITTING BEADED) 9.837.3062.16

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	41 lm/W	
CCT	3400 K	
CRI	54	

1.40	intina	mode
IVIC H	11 11 11 16 1	

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White

Electric

System power: 137 W

Ballast: ECG

Suitable for feed-through wiring

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

LOR

ULOR

Total flux

Total power

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F

83%

5637 lm

137 W

2%