


Product data sheet

PILLAR
7219-0-3-937-XX
UNILAMP



Description PILLAR is a cylindrical shaped light column with unshielded symmetrical light distribution. It is operated with mid-power LED with integrated constant current driver. The PMMA UV stabilized diffuser is used to ensure that the diffuser will not yellow or fade and the desired light output is maintained throughout its life. The simple but effective shape of PILLAR does not clash with surrounding structures in modern architectural spaces. The standard height of this luminaire is presented in this catalogue; however, we can deliver it at different heights for a customized solution. The recommended height is 4 – 6 metres. Anchor bolt kit for ground mounting is available as an accessory. spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA opal diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	73 W	LOR	88%
Lamp flux	10320 lm	Total flux	9063 lm
Luminous efficacy	141 lm/W	Total power	78 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.13 in
Width: 7.13 in
Height: 160.28 in

Adjustability

Fixed

Electric

System power: 78 W
Appliance Class: I

Protection

IP: 65
IK: 07