
Product data sheet

STRIPLINE TW 720LM/M (@2000K) 2000-4000K RA>90
7021983914200
SG ARMATUREN



StripLine is a flexible LED strip system for architectural lighting effects in ceilings, walls, niches and cabinets, for both indoor and outdoor use. Stripline TW comes in two colour temperature ranges: 2700–6500K for traditional TW with the normal circadian spectrum, or 2000–4000K for normal use in homes, including warm and cosy colour temperatures. TW allows you to regulate both the lighting level and colour temperature independently. It provides a premium light quality with high efficiency and great colour rendering. The LED strip is rated to IP54, has tape on the back for mounting and comes with connection cables already assembled. The LED stripe must be fitted in one of the four available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed using the hook. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. The LEDs are positioned at very brief intervals and deliver an even light. StripLine TW can be cut per 5.5 cm to customise each individual installation. When cutting, silicone should be applied to maintain water protection. StripLine TW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch. Light distribution Direct Light technic LED 9W/m 24V 2000-4000K Ra>90 SDCM 3 L80/B10 >50,000 hrs Protection Class III IP54 Materials and finish Optics: Polyuretan (PU) Mounting/Connection Surface, Indoor / Outdoor Module 3.6m Cable 2x5m

Light output 1



1 x LED

Nominal lamp power	9 W	LOR	100%
Lamp flux	720 lm	ULOR	3%
Luminous efficacy	80 lm/W	Total flux	720 lm
CCT	2000 K	Total power	9 W
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in
Width: 0.47 in
Height: 0.12 in

Adjustability

Fixed

Electric

System power: 9 W
Color adjustable
Appliance Class: III

Protection

IP: 54