Product data sheet

INT M LED2200-FW FL BK BKBK
60210854
ZUMTOBEL



LED module for precise, diverse accent lighting in the shop and retail sector; accent/emergency light modules and module inserts can be combined in the installation frame/channel with trim or plaster surround (trimless); lamp(s): 1/36W LED2200-FW; Luminaire or spotlight with FLOOD light distribution; Colour temperature matched to meat goods; Chromaticity tolerance (initial MacAdam): 4; Luminaire luminous flux: 2200 lm, Luminaire efficacy: 61 lm/W; service life: 50000h for luminous flux at 70% of initial value; includes control unit ; multifunctional lamp unit rotates through 360° and swivels in/out (-20°/+90°), ceiling-flush downlight position; with state-of-the-art LED technology; innovative thermal design achieves passive cooling; lamp unit of die-cast aluminium, front ring/mounting plate of polycarbonate; colour combinations of single components (lamp unit/internal luminaire surface/front ring): black/black/black; reflector: polycarbonate, aluminium-sputtered, mirrorbrite and iridescent-free; specular reflector designed for easy replacement and conversion; luminaire wired with halogen-free leads; power connection: 3-pole terminal, through-wiring possible; total power: 36 W; mains voltage: 230V/ 50/60Hz; Simple, tool-free mounting of module in INTRO M installation frame (single, double or triple) or installation channels via locking mechanism, please order separately; Dimensions: 170 x 180 x 146 mm; weight: 1.3 kg; Note on versions: various colour combinations (design personalisations) of single components possible due to modular construction

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	85
Total flux	2200 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	36 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.69 in
Width: 7.09 in
Height: 5.75 in
Weight: 1.3 kg

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 36 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE