

Product data sheet


METROPOLI 2XG24_STRUCTURE WHITE
D20/38.4EP
LUCEPLAN




IP
65

Sobrio e impeccabile, il telaio in alluminio pressofuso contiene il diffusore e dispone di una serie di ottiche intercambiabili che permette di utilizzare a scelta lampadine alogene o fluorescenti, Metropoli viene ora proposta con nuove sorgenti LED per una maggiore efficienza luminosa. Il diffusore è in vetro stampato prismaticizzato o policarbonato opalino (tenuta stagna).


Light output 1




2 x Compact fluorescent lamp			
Nominal lamp power	26 W	Socket	G24D_3
Lamp flux	1800 lm	LOR	55%
Luminous efficacy	13 lm/W	Total flux	1981 lm
CCT	3000 K	Total power	150 W
CRI	85		



2 x Compact fluorescent lamp			
Nominal lamp power	18 W	Socket	G24D-2
Lamp flux	1200 lm	LOR	55%
Luminous efficacy	9 lm/W	Total flux	1321 lm
CCT	3000 K	Total power	150 W
CRI	85		



2 x Compact fluorescent lamp			
Nominal lamp power	11 W	Socket	G23
Lamp flux	900 lm	LOR	55%
Luminous efficacy	7 lm/W	Total flux	990 lm
CCT	3000 K	Total power	150 W
CRI	85		



2 x Halogen low voltage lamp without reflector

Nominal lamp power	70 W	Socket	E27
Lamp flux	1200 lm	LOR	55%
Luminous efficacy	9 lm/W	Total flux	1321 lm
CCT	3000 K	Total power	150 W
CRI	99		

Mounting mode

Wall mounted

Electric

System power: 150 W

Shape and measurements

Length: 4.80 in

Width: 14.78 in

Height: 14.78 in

Protection

IP: 65

Adjustability

Fixed