


# Product data sheet

MEIKE II  
5.902.5567.08  
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 3.00 - 4.50m. - Impact-resistant polycarbonate attachment, UV-stabilized, ice-décor - Impact-resistant polycarbonate cap, UV-stabilized, - Reflector for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodised - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - RAL 9005 last digits as 081 or RAL 7032 last digits as 082 - Order pole, dia. 76mm, separately

## Light output 1



|                    |         |             |         |
|--------------------|---------|-------------|---------|
| 2 x DULUX L-SP     |         |             |         |
| Nominal lamp power | 24 W    | LOR         | 70%     |
| Lamp flux          | 1800 lm | ULOR        | 4%      |
| Luminous efficacy  | 47 lm/W | Total flux  | 2516 lm |
| CCT                | 2899 K  | Total power | 54 W    |
| CRI                | 90      |             |         |

## Mounting mode

Pole top mounted

## Electric

System power: 54 W

## Shape and measurements

Height: 18.50 in  
Diameter: 23.62 in

## Design

Color of housing: Black