


Product data sheet

ZOID BOLLARD
7811-0-3-986-XX
UNILAMP



ZOID a bollard with light emission on one side with glare shield louver. This device constructed with all approved components a high grade nonetheless; body of Zoid is corrosion resistant aluminium. Safety tempered glass is chosen as cover sealant rationale of the model. Zoid falls under Class 2 luminaire. It has glare shield slanted louver through out visibility where lights shine. As mentioned prior components were selected with stamp of approval, even LED engine is selectively high quality. To better protect materials from extreme condition coating with Nano Ceramic film were applied for parties interest. The bollard can be customized to required heights and an anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • White integrated louvers. • GFR PA6.6 Terminal block. • M20 cable gland. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	25 W	LOR	24%
Lamp flux	3170 lm	Total flux	755 lm
Luminous efficacy	127 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 5.31 in
Width: 3.74 in
Height: 35.10 in

Adjustability

Fixed

Electric

System power: 28 W
Appliance Class: II

Protection

IP: 65
IK: 07