



Product data sheet

COMPASS
03.3520/QR-111/100W45°24°8°/75W45°24°/50W24°
FLOS




Luminaire for halogen and high-pressure discharge lamps. Injection-moulded aluminium reflector body with powder-coated finish. Lamp support with die-cast aluminium, black powder-coated heat dissipating element. Thermoplastic recessed ring and screening ring, die-cast aluminium, black powder-coated anti-glare ring. 4 mm. tempered glass cover. Stainless steel fixing brackets.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	G5.3
Lamp flux	589 lm	LOR	100%
Luminous efficacy	12 lm/W	Total flux	590 lm
CCT	4000 K	Total power	50 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	871 lm	LOR	100%
Luminous efficacy	12 lm/W	Total flux	871 lm
CCT	3000 K	Total power	75 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	707 lm	LOR	100%
Luminous efficacy	9 lm/W	Total flux	707 lm
CCT	3000 K	Total power	75 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	977 lm	LOR	100%
Luminous efficacy	10 lm/W	Total flux	980 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1368 lm	LOR	100%
Luminous efficacy	14 lm/W	Total flux	1368 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1089 lm	LOR	100%
Luminous efficacy	11 lm/W	Total flux	1089 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 8.66 in

Diameter: 6.38 in

Adjustability

Tiltable

Electric

System power: 50-100 W

Protection

IP: 23