Product data sheet


ROTAO60 227-2B0K-10GGE/840, W
227-2B0K-10GGE/840
HALLA



IP 20


227-2B0K-10GGE/840, W Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 1140 x 1140 x 65 mm Type of installation: Surface Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 7 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 8 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 9 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Light output 10 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	734 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.56 in

Diameter: 44.88 in

Adjustability

Fixed

Electric

System power: 64 W

Appliance Class: I

Protection

IP: 20