


# Product data sheet

MICROSEGNO SQ 32 24V 1 X 1.5W 31° 3000 K  
GH1227.BAMT300EL  
GHIDINI



Series of recessed lighting fixtures characterized by a small dimension and shallow recess depth. Available in various sizes, they are designed for lighting facades, little walls, plants, shrubs and other little architectural elements in general thanks to a wide range of optics and wattages. The body and diffuser closure ring are constructed of high oxidation resistant aluminum alloy which is subjected to anodization treatment, guaranteeing maximum protection over the years. Silicone gaskets ensure maximum sealing in all operating and temperature conditions. The ultra transparent tempered sodium calcium glass diffuser ensures maximum light transmittance and is finished with a silkscreen border. The external finishing frame is in machined stainless steel. The product is equipped with the Ghidini water-lock system which prevents condensation from the power cable due to the alternating on and off cycles. The product is installed with a polypropylene rough-in housing that prevents the contact of the fixture directly with the ground and allows the necessary space for wiring. The product can be walked over and can be installed in areas not permitted for traffic. Not suitable for installation in swimming pools or fountains.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	90
Total flux	81 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	1.5 W

## Mounting mode

Floor recessed

## Shape and measurements

Length: 1.26 in  
Width: 1.26 in  
Height: 0.10 in

## Adjustability

Fixed

## Electric

System power: 1.5 W  
Appliance Class: III

## Protection

IP: 68