## Product data sheet

SANTOS KREIS 311715.0042.1

RZB







Series: Santos Kreis Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, white, powder-coated. Diffuser fastening: decorative ring with spring system. Diffuser: domed opal glass plate, frosted. Decorative ring: metal. Available Colours: nickel, matt Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 310, H 87 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 680lm System power: 14W Beam Angle: 114° Number of fittings B10A: 10 Number of fittings B16A: 27 Number of fittings C10A: 28 Number of fittings C16A: 45 Inrush current: 27A Unified Glare Ratio: 19,4 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14 W	CRI	80
Total flux	680 lm	LOR	100%
Luminous efficacy	49 lm/W	ULOR	4%
		Total power	14 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.43 in Diameter: 12.20 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 20