

Product data sheet


SINUS.QUIET SUSP. 'Z' WHITE PRISM. 1174MM
R33Z117-QAWSE1940L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP
40


low output LED 4000K CRI 90 42,8W 5699lm' DALI 'Values without foil [Luminaire is delivered with optional satined-foil for increased homogeneity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% <https://katalog.planlicht.com/en-gb/fam-sinus-quiet/>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	712 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	34%
		Total power	5.35 W

Mounting mode

Pendant

Shape and measurements

Length: 46.22 in

Width: 46.22 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 42.8 W

Protection

IP: 40