



# Product data sheet

TOMMASO  
691422  
FLOS



• Outdoor luminaire for installation on wall. • Configuration: die-cast aluminium structure . EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered sandblasted glass; silicone gasket.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	200 W	Socket	R7S
Lamp flux	3520 lm	LOR	41%
Luminous efficacy	7 lm/W	ULOR	21%
CCT	2900 K	Total flux	1458 lm
CRI	100	Total power	200 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 11.81 in  
Width: 4.33 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 200 W  
Appliance Class: I

## Protection

IP: 54  
IK: 08