Product data sheet

SIDELITE ECO
312142.002
RZB



IP 40 IK 02

Series: Sidelite ECO Type of Protection: IP 40 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Luminaire frame aluminium, powder-coated, surface-mounted housing sheet steel powder-coated, diffuser plastic opal, diffuser and light guide made of non-yellowing PMMA, lateral light emission with LED, converter integrated. Lamp (LED) included. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 295, B 295, H 49 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1800lm System power: 23W Beam Angle: 115° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 23,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23 W	CRI	80
Total flux	1800 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	23 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.61 in
Width: 11.61 in
Height: 1.93 in

Adjustability

Fixed

Electric

System power: 23 W

Protection

IP: 40
IK: 02