Product data sheet

LADOR 15 CLUSTER COLUMN PROJECTORS
LD-20023-N-8030
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear - Maximum wind load resistance is 140 km/h - Surge protection 10kV

Light outputs 1..4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3641 lm	LOR	100%
Luminous efficacy	104 lm/W	ULOR	50%
		Total power	35 W

Mounting mode

Pole integrated

Shape and measurements

Length: 5.75 in
Width: 5.75 in
Height: 157.48 in
Weight: 24.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 140 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C