


Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE, SPOTLIGHT
TL2103506-33-30_16W
SCHMITZ | WILA



Tentec accent LED 3000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: TL2103506-33-30
Operating technology: independent driver required Light Technique Light module 361° rotatable, with integrated rotation stop Tilt range from 0-30° CRI > 80 High chromaticity stability with 3SDCM (initial) Constant colour temperature 3000 K Lifetime 50.000 h (L70) Reflector, high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016 Operating and assembly technology Order LED gear box separately Gear boxes suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 16 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 1460 Lm System Efficiency: 81 Lm/W Half-peak Divergence α : 60° Number Luminaires LZ: 0.08 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q10 Length: 127 mm Width: 127 mm Cut-out length: 120 mm Cut-out width: 120 mm Installation Depth RD: 140 mm Total Weight: 0.6 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record TL2103506-33-30_16W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	18 W	LOR	100%
Lamp flux	1460 lm	Total flux	1460 lm
Luminous efficacy	81 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.00 in
Width: 5.00 in
Height: 5.51 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 18 W
Appliance Class: II

Protection

IP: 20