



Product data sheet

X-LINE SLIM SURFACE LED 2200 MICRO-PRM E 24 840 / L-578MM
19.4183.9121.24
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is aluminum. Colour - anodised aluminum. Luminaire dimensions: 578 x 48 x 70 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 74,32%. Beam angle: (C0-C180) / (C90-C270) - 88,4° / 86°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 1730,1 lm. Power of luminaire: 12,4 W. Luminaire's light efficiency: 132,6 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 46 (B10), 74 (B16), 72 (C10), 115 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	12.4 W	LOR	83%
Lamp flux	2338 lm	Total flux	1951 lm
Luminous efficacy	189 lm/W	Total power	12.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.76 in

Width: 1.89 in

Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 12.4 W

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F