Product data sheet

GUIDELED SL 13812 1-8H/D CGLINE+ (SET TO 3 H OPERATION) 40071353279

EATON EMERGENCY LIGHTING








• LED self contained luminaire with automatic test for reduced inspection effort • Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation • For autonomous installation or connection to the CGLine+ monitoring system • Environmentally-friendly due to modern lithium ion technology • Low operating costs via low connected load • Minimum maintenance effort via high LED service life (50,000 hours) • Available with special optics for escape route illumination or open-area illumination • High spacing via double optics technology and highly efficient High Power LEDs • Simple fault analysis and status display via bicolor LED and testing button • 1 minute switch-back delay after mains return • Blocking function prevents unintended discharge during idle operating times (only with CGLine+ WEB-Controller)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.7 W	CRI	70
Total flux	105 lm	LOR	100%
Luminous efficacy	16 lm/W	Total power	6.7 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 6.77 in Width: 6.77 in Height: 1.57 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 6.7 W Appliance Class: I

Information regarding emergency functions

Emergency lighting only

Emergency power supply: Single battery 1 h, Single battery 3 h, Single

battery 8 h

Emergency sign: N/A

Protection

IP: 41

IK: 03