Product data sheet


MAX MEDIUM DOUBLE EMISSION
AI21-13X9M2OSZ5
LEDSC4



IP 66 IK 10


LedsC4 Max Medium Double Emission AI21-13X9M2OSZ5 Wall fixture for outdoor use. For uplighting and downlighting. Structure material: Aluminium. Structure finish: Urban grey. Diffuser material: Glass. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 1.16 Product width or diameter (mm): 62 Product height (mm): 135 Product aperture (mm): 85 Class 1. Glow wire test: 850. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 13W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 8.2. Photobiological risk: RG2. % de Flickering: <3%. Real flux (lm): 918. Real lm/W: 59. Voltage / frequency range: 220-240V/50-60Hz. Voltage: 18. Equipment included: Yes. Total power: 15.5. Power factor: 0.92. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	15.5 W	LOR	100%
Lamp flux	918 lm	ULOR	50%
Luminous efficacy	59 lm/W	Total flux	917 lm
CCT	4000 K	Total power	15.5 W
CRI	80		



1 x LED

Nominal lamp power	15.5 W	LOR	100%
Lamp flux	918 lm	ULOR	50%
Luminous efficacy	59 lm/W	Total flux	917 lm
CCT	4000 K	Total power	15.5 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 2.76 in
Width: 3.35 in
Height: 5.31 in

Adjustability

Fixed

Electric

System power: 15.5 W
Appliance Class: I

Protection

IP: 66
IK: 10