
Product data sheet

LD10238 13.3W 700MA WWB GS
LD10238-N1-700-WWB-GS
LIGHTGRAPHIX



LD10238 Constant Current surface mount spotlight. 13.3W 700mA 65° Extra wide with Ground Spike (400mm total length). The LD10238 is a compact, high powered surface mounted spotlight, suitable for use in interior or exterior applications. It can be specified with a wide range of options allowing it to suit most project requirements. Available LED engines include White, Tunable White, CLR LEDs offering multiple outputs, excellent CRIs of 90+ and colour temperatures between 2200K-5000K. A choice of mounting methods, such as a bracket, mount base, tree strap or adjustable ground spike. The use of a matt black inner baffle, recessed LED, single optic and optional honeycomb louvre ensure excellent low glare illumination. With a large selection of paint finishes available and fixing options, the LD10238 can blend discreetly into many environments. This is a very tough, high quality fitting, machined from high grade materials, ensuring excellent thermal and light output performance

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.3 W	CRI	93
Total flux	891 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	13.3 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 3.62 in
Diameter: 2.36 in

Adjustability

Rotatable, Tiltable, Free

Design

Material impression: Aluminum, Glass
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 13.3 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...77°F