

Product data sheet


RAY T DIFF.METAL.NRO
F5911030
FLOS



IP
20

Table lamp providing diffused lighting. Steel tube (10 mm diam.) structure, welded, brushed and chrome-plated. Diffuser support disk in die-cast, polished and chrome-plated Zamak alloy. White injection-molded PA6 (nylon) lamp cover. Injection-molded PC (polycarbonate) inner diffuser in 3% opal color. Transparent injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. Resistive dimmer wired on cord for 0-100% light adjustment. Power cord with black PVC/PVC (flat) sheath (1500 mm) Net weight glass diffuser 6,7 kg metal diffuser 3,7 kg.

Light output 1



1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 150 W | Socket | E27 |
| Lamp flux | 2500 lm | LOR | 43% |
| Luminous efficacy | 7 lm/W | ULOR | 13% |
| CCT | 2821 K | Total flux | 1085 lm |
| CRI | 99 | Total power | 150 W |

Mounting mode

Table luminaire

Shape and measurements

Length: 14.10 in
Width: 14.17 in
Height: 26.38 in

Adjustability

Fixed

Electric

System power: 150 W

Protection

IP: 20