

Product data sheet

DKN KREIS
10320.002
RZB




IP
40

IK
02

Series: DKN-Kreis, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: ~ 250 / 0 - 60 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 250, H 110 Lamp: 1 x E27 max. 60 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 74°/84°/89°/70° Unified Glare Ratio: 18,2 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	23 W	Socket	E27
Lamp flux	1570 lm	LOR	80%
Luminous efficacy	55 lm/W	ULOR	28%
CCT	2700 K	Total flux	1256 lm
CRI	80	Total power	23 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.94 in
Diameter: 9.84 in

Adjustability

Fixed

Electric

System power: 23 W

Protection

IP: 40
IK: 02