


# Product data sheet

48 CAMINO LED OUTDOOR LIGHT FITTING  
48 3203A RFLOU (48004 0044)  
SCHUCH



LED outdoor light fitting, CAMINO, 70 W, 10000 lm, 143 lm/W, Class II, IP66, asymmetrical beam, 4000 K, CRI $\geq$  70, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Ready for Light Management Systems (RFL), socket on the top and at the bottom (RFLOU), Pane Safety glass clear, Housing Die-cast aluminium, Colour grey, DB702N. LED outdoor light fitting of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with ECG, LED modules, optics and frameless tempered safety glass pane, hinged and detachable from the lower part. Lower part with integrated pole mounting system, adjustable inclination, cable entry, strain relief and integrated pressure compensation system (dirt-resistant). Zhaga socket on the top and/or bottom of the housing. Electro kit carrying all electrical components, completely removable by unplugging isolating plug connection. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Universal die-cast aluminium pole mounting system for pole-top Ø 60/76mm and side-entry mounting Ø 42/60mm. The light fitting is prepared for later upgrades with components of a light management system with Zhaga socket. RFL luminaires from Schuch use D4i control gear without exception. All D4i Zhaga Book 18 certified controllers and D4i Zhaga Book 18 certified sensors available on the market can be used in combination with RFL luminaires from Schuch. However, controllers and sensors that do not comply with the D4i standard may restrict the functionality of the luminaires and components. In addition, in individual cases, such non-certified components may cause damage to both the luminaires and the components. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 610,00 mm, Width/Diameter 251,00 mm, Height 157,00 mm, Net weight 7,50 kg.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 70 W     | CRI         | 70     |
| Total flux         | 9999 lm  | LOR         | 100%   |
| Luminous efficacy  | 143 lm/W | ULOR        | 7%     |
|                    |          | Total power | 70 W   |

## Mounting mode

Pole top mounted, Pole integrated

## Shape and measurements

Length: 24.02 in  
Width: 9.88 in  
Height: 6.18 in

## Adjustability

Fixed

## Electric

System power: 70 W  
Appliance Class: I

## Protection

IP: 66  
IK: 09  
Designation labels: CE, ENEC